

6kg dry powder Fire Extinguisher (stored pressure)



www.DX-marine.com

DESIGN BY DX-MARINE



Type : PSMPZ6A/5

Extinguishant : ABC30 dry powder

Capacity (kg): 6

Propellant: Dry Nitrogen(N2)

Cylinder Diameter (mm) : 160

Overall Height (mm): 565

Approx Full Weight (kg): 9.8

Working Temp. Range:

-30°C to + 60°C

Working Pressure (20°C) : 15 Bar

Test Pressure: 27 Bar

Burst Pressure: Exceeds 55 Bar

Approx Discharge Range (m): >4

Approx Discharge Time (sec): ≥15

Fire Rating: 43A 233B C

Fire Class: A B C

Cylinder Specification: CE EN3-8

Discharge Assembly: PVC Nozzle

Mounting: Wall hanger

Operating Head / Valve: Brass nickel plating

Paint Finishing: RAL 3000 Flame Red

Thermoset polyester

Manufactured & Certified to: CE EN 3-7 + EN 3-8

Approved: MED CE EN3



Bottle holder

AS 1851		SERVICE RECORD											
YEAR	JAN	FEB	MAR	APR	MAY	JUNE	JULY	AUG	SEPT	OCT	NOV	DEC	
19													
20													
21													
22													
23													
24													
25													
26													

Service record

Jiangsu Dingxiang Marine Equipment Co.,LTD.

Professional fire fighting & life saving equipment manufacturer