

6L frying pan fire extinguisher (stored pressure)

www.DX-marine.com

DESIGN BY DX-MARINE



Type : PSMFZ6/2

Extinguishant: INILAM AX & SC-6

Capacity (L): 6

Propellant: Dry Nitrogen(N2)

Cylinder Diameter (mm): 160

Overall Height (mm): 555

Approx Full Weight (kg): 9.8

Working Temp. Range: 0°C to + 60°C

Working Pressure (20°C): 10 Bar

Test Pressure: 27 Bar

Burst Pressure: Exceeds 55 Bar

Approx Discharge Range (m): >4

Approx Discharge Time (sec): ≥15

Fire Rating: 34A 183B 40F

Fire Class: A B F

Cylinder Specification: CE EN3-8

Discharge Assembly: PVC Nozzle

Mounting: Wall hanger

Operating Head / Valve: Brass nickel plating

Paint Finishing: RAL 3000 Flame Red

Thermoset polyester

Manufactured & Certified to: CE EN 3-7 + EN 3-8

Approved: MED CE EN3



Bottle holder

AS 1851 SERVICE RECORD												
YEAR	JAN	FEB	MAR	APR	MAY	JUNE	JULY	AUG	SEPT	OCT	NOV	DEC
19												
20												
21												
22												
23												
24												
25												
26												

Service record

Jiangsu Dingxiang Marine Equipment Co.,LTD.

Professional fire fighting & life saving equipment manufacturer