

# 9kg dry powder Fire Extinguisher (cartridge operated)



[www.DX-marine.com](http://www.DX-marine.com)  
DESIGN BY DX-MARINE



Type: PSMPG9

Extinguishant: ABC40 dry powder

Capacity (kg): 9

CO2 Gas Cartridge (g): 150

Cylinder Diameter (mm): 180

Overall Height (mm): 650

Approx Full Weight (kg): 14

Working Temp. Range:

-30°C to + 60°C

Test Pressure: 30 Bar

Burst Pressure: Exceeds 55 Bar

Approx Discharge Range (m): >4

Approx Discharge Time (sec): ≥15

Fire Rating: 43A 233B C

Fire Class: A B C

Cylinder Specification: CE EN3-8

Discharge Assembly: PVC Nozzle & Spray bucket

Mounting: Wall hanger

Operating Head / Valve: Brass nickel plating

Paint Finishing: RAL 3000 Flame Red

Thermoset polyester

Manufactured & Certified to: CE EN 3-7 + EN 3-8

Approved: MED CE EN3



Bottle holder

| AS 1851 |     | SERVICE RECORD |     |     |     |      |      |     |      |     |     |     |  |
|---------|-----|----------------|-----|-----|-----|------|------|-----|------|-----|-----|-----|--|
| YEAR    | JAN | FEB            | MAR | APR | MAY | JUNE | JULY | AUG | SEPT | OCT | NOV | DEC |  |
| 19      |     |                |     |     |     |      |      |     |      |     |     |     |  |
| 20      |     |                |     |     |     |      |      |     |      |     |     |     |  |
| 21      |     |                |     |     |     |      |      |     |      |     |     |     |  |
| 22      |     |                |     |     |     |      |      |     |      |     |     |     |  |
| 23      |     |                |     |     |     |      |      |     |      |     |     |     |  |
| 24      |     |                |     |     |     |      |      |     |      |     |     |     |  |
| 25      |     |                |     |     |     |      |      |     |      |     |     |     |  |
| 26      |     |                |     |     |     |      |      |     |      |     |     |     |  |

Service record

**Jiangsu Dingxiang Marine Equipment Co.,LTD.**  
**Professional fire fighting & life saving equipment manufacturer**